

EE-327

NEW

❖ 600TV Lines
❖ WDR
❖ 3D-DNR
❖ D&N Support

IP69K Premium Vandal Dome Camera



FEATURES

- IP69K Vandal dome housing
- 1/3 inch Vertical Double Interline CCD
- Advanced WDR Support
- High Resolution of 600TV lines
- Day&Night capability with high sensitivity of 0.0002 Lux
- HSBLC (High-light Suppress BLC)
- Sens-up (128x) / Low Illumine light
- Privacy Zone Masking : 8 zones
- Digital 8x zoom
- Wall or Ceiling mount through internal 3-Axis camera bracket
- Surface or flush mounting through internal 3-Axis camera bracket
- Safety strap holds dome cover in place while making adjustments
- Easy operation by on screen display
- Extra video out
- OSD menu control with mini joystick

STRUCTURAL FEATURES

- Minimized the cable twist by positioning all the camera components inside the Gimbal.
- It dramatically reduces any possible troubleshooting by cable disconnection or contact error.
- Easy Maintenance with all-in-one PCB for OSD board Power and Balun board
- Optimized design to have FAN / HEATER / IR inside Gimbal
- No need for any tools to handle the Gimbal and adjust the camera angle by using mechanical tension.
- Ball type Gimbal preventing from parts' external exposure.
- Built-in light inside of housing to help user find OSD button & extra video out in dark area.

SPECIFICATIONS

MODEL	EEN-327	EEP-327
Power Input	DC 12V	
Power Consumption	150mA	
Image Sensor	1/3 inch Vertical Double Interline CCD	
Sync.	2:1 Interlace	
Scanning Synchronization	Internal / Line-Lock (External Sync Input)	
Video Out	1.0 Vp-p Composite Signal (750hm)	
WDR	60dB (TIN/P-327 only)	
Auto Gain Control	OFF / LOW / MIDDLE / HIGH	
Exposure	ALC / ELC	
Electric Shutter	1/60~1/90,000	1/50 ~ 1/90,000
Day /Night	True Day and Night (Auto / Day/ Night/ Ext/ D&N)	
Min.Illumination	0.2Lux/ 0.0002Lux (Sens-Up Auto)	
Resolution	600TV Lines	
White Balance	ATW / AWC / Manual (1,700°K~11,000°K)	
Backlight Compensation	BLC / WDR / HSBLC	
3D-DNR	OFF / LOW / MIDDLE / HIGH	
Privacy Masking	8 Zones	
Digital Zoom	8X	
EIS	ON /OFF	
Digital Effect	OFF/ V-Flip / Mirror / Rotate	
Sharpness	Adjustable	
Operation Temperature	-10°C ~ + 50°C	
Storage Temperature	-20°C ~ +60°C	
Weight	1.5Kgs	

OPTIONAL MODEL

- EEN-327A / EEP-327A : AC24V with balun
- EEN-327AF / EEP-327AF : AC24V with balun and Fan
- EEN-327AH/ EEP-327AH : AC24V with balun and Heater
- EEN-327AFH / EEP-327AFH : AC24V with balun, Fan and heater

DIMENSIONS

Unit : mm

